

#### Definition

Single metal barrier for lateral side. System formed by a triple wave barrier and C posts 1,905 metres apart.

### **Impact Tests**

TL-4 according to MASH



Test: 4-10 Passenger car 1,100 Kg - 100 km/h-25°

Test code: MASH067 Date: january 2022

Accredited laboratory: AISICO (Italy)



Test: 4-11Pick-up 2,270 kg - 100 km/h - 25°

Test code: MASH066 Date: january 2022

Accredited laboratory: AISICO (Italy)



Test: 4-12 Truck 10,000 kg - 90 km/h - 15°

Test code: MASH065 Date: january 2022

Accredited laboratory: AISICO (Italy)

## Performance parameters

Containment Level

TL-4

Dynamic Deflection

0,9

Severity


Preferred




# Components for sections of 3,81 m

Item	Part	Uds
1	4 m thrie-beam guardrail (punched at 2 and 1.33 meters). t. 2.5 mm	1
2	C post -125x75 mm of 1,800 mm	2
		_
3	Round head bolt M16x30, with nut	12
		_
4	Hexagon head cap bolt DIN 933 M10x40	4
5	Washer Ø17x35x4 mm	12
6	Washer 100x40x5 mm, with hole Ø11 for M10	8
7	Nut DIN 934 M10	4
8	Reflector	1

### **Fasteners**





Detail of joint in intermediate post